



Product Features

- ANSI standard 156.2 Grade 3 (200,000 Cycle Count)
- KW1 standard keyway, SC1 keyway optional
- Rekeyable for master and construction Keying
- Adjustable 2-3/8" and 2-3/4" backset

- Fits wood or metal doors from 1-3/8" to 1-3/4" thick
- Reversible non-handed Levers
- Deadbolts have full 1" Throw
- Lifetime Limited Warranty
- Easy Installation



Standard Features / Specifications

Door Prep	Cross bore 2-1/8", Edge bore 1" Latch face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/8" - 1-3/4" Doors standard 2-1/4" Doors, extension kit option available
Cylinder	KW1 5-pin standard, SC1 5-pin optional Entries packed KA5
Faceplates	1" x 2-1/4" Round corner

Strikes	1-3/4" x 2-1/4" Round corner, full lip Other options available
Bolt	Deadbolt: 1" Throw, Knob/ Lever: 1/2" Throw
Door Handing	Non-Handed
ANSI/BHMA	Grade 3 Certified
KEYS	2 Per Lock

Function Availability

Model No. Description Keyed Entry: Both Knobs/Levers locked or unlocked by key outside 100T or turnbutton or pushbutton inside. Privacy/Bed & Bath: Both Knobs/Levers locked or unlocked by 102T turnbutton or pushbutton inside – F76. 101T Passage/Hall & Closet: Both Knobs/Levers always unlocked – F75. Single Dummy/Surface Mounted: Knob/Lever no operating parts. 115 For use on doors where only a pull is needed. Single Cylinder: Deadbolt operated by key outside and turnbutton 200S inside. 210S Double Cylinder: Deadbolt operated by key on both sides.

Available Finishes



US3 Bright Brass



US5 Antique Brass



US15 Satin Nickel



US10B Oil Rubbed Bronze



US10BE Oil Rubbed Bronze Edged



US19 Matte Black



AS Antique Silver



US26 Bright Chrome

